



General Specifications

Power Requirement	- VDC at unit	7-18 VDC
Current Consumption	- Idle	63mA
	- Peak	168mA
Card Read Range	- Metric	20mm - 40 mm
	- USA	0.8" - 1.6"
Operating Temperature	- Metric	-20°C to +65°C
	- USA	-4°F to +149°F
Relative Humidity	- % max	90%, operating non condensing
Reader Dimensions	- Metric	156mm x 98mm x 50mm
	- USA	6.14" x 3.86" x 1.97"
Status LED's	- Colour	Red & Green
Audible Tone		Tone on matching software key and wired buzzer control
Colour finish		Charcoal
LCD		8 x20 characters
LCD Messaging		Standard Card & PIN
		Read/Access Messaging
		Custom messaging in RS485 Mode
Keypad		Backlit, 16 Button,
Certifications/Ratings		CE, FCC, C-tick, ROHS, IP65

BT853 M2000

Dual factor authentication and optional Alarm Pad function with an LCD display for user feedback and messaging.

The BT853 series reader is designed for medium to high security applications where two forms of authentication (card & PIN) are required for access. Featuring a two line LCD display providing visual indication of system status, access feedback and system messaging and a ready wakeup sensor on user approach. The BT853 series is available in several technologies and in three switchable modes of operation: Card & PIN, Card Only, PIN only.

Model Features

Model	Technology			Authentication Factors		Encode			Encryption		Sector Keys		13.56MHz Credential type and option				Output Protocol			Other																	
	Mifare Classic	Mifare Plus	DESfire	Card	Biometric	Keypad	CSN/UID	Sector	Application	Random UID	Diversified Keys	Crypto 1	3 DES	AES (optional)	MiPASS 2	MiPASS 3	Customisable	ISO14443A	ISO14443B	Mifare 1K & 4K	Mifare Plus 2K & 4K	DESfire EV1 4K & 8K	Wiegand 32 Bit	Wiegand 26-199 Bit	Encrypted RS485*	Read / Write	PIC = PIN on Card	Custom PIN Output	Indoor / Outdoor	Tamper option							
BT853																																					
BT853-A																																					
BT853-1	✓			✓		✓	✓																														
BT853-2	✓			✓		✓	✓	✓							✓												✓	✓									
BT853-3	✓			✓		✓	✓	✓									✓	✓								✓	✓	✓									
BT853-4		✓		✓		✓	✓	✓							✓												✓	✓									
BT853-6	✓	✓	✓	✓		✓	✓	✓									✓	✓								✓	✓	✓									

* Requires High Security Module (HSM) AES 128bit encryption

Contact BQT Solutions for more information or a discussion on custom options available, visit our website www.bqtsolutions.com for your nearest office.

[MAR2015] All specifications are subject to change without notice. Contact BQT Solutions to confirm. BQT Solution and miPASS are registered trademarks. ©2015.